

Product Information Facade blind FM 100

Heat protection due to reflection of the heat radiation in front of the facade

Harmonious facade design due to the same box design like
the awnings V!VA and the conservatory blind Tenda

Up-to-date colours and numerous designs

Easy operation




Models



FM 101 - bar guided



FM 102 - barguided + tilt-out unit



FM 103 - cable guide



FM 104 - rod guide



FM 105 - drop-arm awning

Limit Sizes

	Type of operation	Covering	max. surface (m ²)	min. width (mm)	max. width (mm)	min. height (mm)	max. height (mm)
FM 101	Standard-electric drive	Soltis 92/86	9	540	3500	500	4500
	Standard-electric drive	Sonstige *)	9	540	3500	500	3000 **)
FM 102	Standard-electric drive	Soltis 92/86	9	540	3000	1200	4500
	Standard-electric drive	Sonstige *)	9	540	3000	1200	3000 ***)
FM 103	Standard-electric drive	All	9	540	3000	500	3000
FM 104	Standard-electric drive	All	9	540	3000	500	3000


	Type of operation	Covering	max. surface (m ²)	min. width (mm)	max. width (mm)	Projection
FM 105	Standard-electric drive	All	9	540	3000	600, 900, 1200

Limiting of the width for all designs	max. surface (m ²)	width (mm)
Minimum width with radio control		720
Maximum width with coupling full-length cover	13,5	4500
Maximum width with coupling divided cover	27	9000 (bei FM 101: 10500 mm)


Types of installation

Dimensions of the box:


112 x 143 mm



placed upon the side guide rail



with box bracket



with installation profile

*) Acrylic fabrics, All-weather, Liberty, Sunsilik, Glastex, Sunless, Twilight, Transolair

**) with a width up to 1220 mm a maximum height of 4500 mm is possible
(applies only for acrylic fabrics, All-Weather, Liberty, Sunsilik)

***) with a width up to 1250 mm a maximum height of 4500 mm is possible
(applies only for acrylic fabrics, All-Weather, Liberty, Sunsilik)

Qualified company:

Head Office:
HELLA Sonnen- und Wetterschutztechnik GmbH
 A-9913 Abfaltersbach 125
 T. +43 (0)4846 / 65 55-0
 F. +43 (0)4846 / 65 55-134
 E: office@hella.info

www.hella.info