

Product Information Interior Venetian Blinds 16, 25 mm

Sun- and view-protection
Design element
Control of sunlight
Different types of installation
Easy operation



ISOLINE without tensioning wire (IF)**ISOLINE with tensioning wire (ISO)**

- Width of slats 16 or 25 mm
- Installed on casement
- Chain operated, Electric drive available (additional charge)

Blind for double-glazed window (VF)

For installation between glass panels

- Width of slats 16 or 25 mm
- Draw-cord operated
- Adjustment of slats via tilting wand

Interior Venetian blind without tensioning wire (IF)**Interior Venetian blind with tensioning wire (IF)**

- Width of slats 16 or 25 mm
- Various operating modes available

Different methods of installation with tensioning wire

Tensioning shoe
for installation on the glass frame



Tensioning angle bracket
for installation on window casement

Operating modes

Control with draw-cord,
tilting of slats via tilting wand




Control and tilting of slats
via draw-chain, chain outlet
in front



Control and tilting of slats
via draw-chain, lateral chain outlet



Control and tilting of slats
via draw-chain, lateral chain
outlet (Model ISOLINE)



Electric driven



Control and tilting of slats
via hand crank

Fields of application

Complete Height (mm)	Package Height (mm) Slat 25 mm	Package Height (mm) Slat 16 mm
1000	60	90
1500	70	100
2000	80	120
2500	95	140
3000	105	-
3500	120	-

Model	Slats 16/25 mm		Slats 16 mm		Slats 25 mm	
	min. width	max. surf.	max. width	max. height	max. width	max. height
VF SZD	240	3	1500	2500	1500	3000
ISO (IF) SZV	300	3	2100	2500	2100	3000
ISOLINE KZ	390	2,5	2000	2500	2000	2500
ISOLINE KZ bis FH 2000 mm	320	2,5	2000	2000	2000	2000
ISOLINE EL	730	5	2700	2500	3000	3500
ISOLINE EL bis FH 2000 mm	590	5	2700	2000	3000	2000
ISOLINE EL mit Funk	980	5	2700	2500	3000	3500
ISOLINE EL bis FH 2000 mm mit Funk	710	5	2700	2000	3000	2000
ISO (IF) KZV	480	4	2700	2500	3000	3500
ISO (IF) KZV bis FH 2000 mm	430	4	2700	2000	3000	2000
ISO (IF) KZS	390	4	2700	2500	3000	3500
ISO (IF) KZS bis FH 2000 mm	310	4	2700	2000	3000	2000
ISO (IF) KZS	330	4	2700	2500	3000	3500

Abbreviations - types of operation

SZD = Cord operation
SZV = Cord operation, cord exit at the front
EL = Electric drive

KZ = Draw-chain operation
KZV = Draw-chain operation, chain exit at the front
KZS = Draw-chain operation, lateral drawchain exit

Qualified company:

Head Office:
HELLA Sonnen- und Wetterschutztechnik GmbH

A-9913 Abfaltersbach 125

T. +43 (0)4846 / 65 55-0

F. +43 (0)4846 / 65 55-134

E: office@hella.info

www.hella.info